LINN CUSTOM 2K SERIES

TECHNICAL SPECIFICATION

Custom Installation Loudspeakers

104C-R / 104C-S

▌	Launch date	January 2007
▌	Type	3-way loudspeaker with a sealed acoustic enclosure
▌	Frequency response	100 Hz – 20 kHz +/- 3 dB (passive & AKTIV)
▌	Input impedance	6 Ω
▌	Sensitivity	87dB/1W/1m
▌	Wiring options	Single wire, AKTIV[1]
▌	Drive units	16 mm soft dome tweeter 30 mm soft dome mid 100 mm screened bass unit
▌	Product Dimensions	104C-R: 200mm (Ø) / 104C-S: 200mm (H) x 200mm (W) 104C-R: 7.9 inches (Ø) / 104C-S: 7.9 inches (H) x 7.9 inches (W)
▌	Cut-out Dimensions	176 mm (Ø), 93 mm (D) 6.9 inches (Ø), 3.6 (D) inches
▌	Mounting depth	93 mm, 3.6 inches
▌	Weight	1.6 kg 3.6 lbs
▌	Fire Rating	UL94V0

104C-R









104C-S









AKTIV Cards for Linn Custom 2K

CHAKT38	CHAKRA AKTIV Module for Linn Custom 2K 106C Bass (mono)
CHAKT39	CHAKRA AKTIV Module for Linn Custom 2K 106C Mid (mono)
CHAKT40	CHAKRA AKTIV Module for Linn Custom 2K 106C Treble (mono)
CHAKT41	CHAKRA AKTIV Module for Linn Custom 2K 104C-R & 104C-S Bass (mono)
CHAKT42	CHAKRA AKTIV Module for Linn Custom 2K 104C-R & 104C-S Mid (mono)
CHAKT43	CHAKRA AKTIV Module for Linn Custom 2K 104C-R & 104C-S Treble (mono)